Instantaneous RV Hot Water System

Never runout of Hot Water again!

Designed for Australian conditions
 Door opening correctly for right hand drive
 Doors available in Black & white
 Improved dust sealing

nlimited hot water no waiting time for water to reheat Second digital controllers available for convenience in your caravan or motorhome (sold Separately) • State of the art electronic 12Volt operation • LPG fueled

Field tested in Australia for 1 year
 All units tested In Australia prior to sale
 Installation cut out size 330 x 330 x 450mm

 Weight: 13.5kg
 1 Year Warranty

DOOR OPENS CORRECTLY FOR RIGHT HAND DRIVE

Black & White



Doors Availiable FOR MOREINFORMATION AND YOUR NEAREST STOCKIST PLEASE VISIT

• <mark>8</mark> 8

Instantaneous RV Hot Water System

9

11

FOGATTI



SPECIFICATIONS

Model	FS06B1
Gas Type	Universal LPG
Nominal Heat Input (Btu/hr)	42,000
Minimum Heat Input (Btu/hr)	20,000
Orifice Drill Size	0.91mm for LPG
Gas rated pressure	2.75kPa
Maximum Manifold Pressure	1.54kPa
Minimum Manifold Pressure	0.37kPa
Maximum Water Pressure	800kPa
Minimum Water Pressure	100kPa
Water Heating Capacity(temp rise 25K)	6LPM
Maximum Water Temp	51°C
Power Supply	12VDC, RV Battery
Total Input Current (A)	10 AMP
Shipping Dimensions(W*H*D)	380mm x 380mm x 365mm
Cut Out Dimensions(W*H*D)	330mm x 330 x 450mm